

## CLAIMS:

1. A control apparatus for enabling a user to control by spoken commands a function of a processor-controlled machine couplable to speech processing apparatus, the control apparatus comprising:

receiving means for receiving dialog interpretable instructions derived from speech data processed by the speech processing apparatus;

dialog communication means for interpreting received dialog interpretable instructions using a dialog compatible with the processor-controlled machine and for communicating with the processor-controlled machine using the dialog to enable information to be provided to the user in response to received dialog interpretable instructions, thereby enabling a dialog to be conducted with the user;

dialog determining means for determining from information provided by the processor-controlled machine the dialog to be used with that processor-controlled machine; and

machine communication means for communicating with the processor-controlled machine to cause the processor-controlled machine to carry out a function in accordance with the dialog with the user.

T04290"2426860

5 2. A control apparatus according to claim 1, wherein the control apparatus is couplable to a network and the dialog determining means is arranged to determine the location on the network of a file for that dialog.

3. A control apparatus according to claim 1, further comprising storing means for causing the dialog to be stored in a dialog store of the control apparatus.


10 4. A control apparatus according to claim 1, comprising means for determining, using information provided by the processor-controlled machine, functions available on that machine.

15 5. A control apparatus comprising a JAVA virtual machine for enabling a user to control by spoken commands a function of a processor-controlled machine couplable to to speech processing apparatus, the JAVA virtual machine comprising:

20 receiving means receiving dialog interpretable instructions derived from speech processed by the speech processing apparatus;

25 dialog communication means for interpreting, using a dialog compatible with the processor-controlled machine, received dialog interpretable instructions,

204230" 2442660



a dialog communicating means for communicating with the processor-controlled machine using the dialog to enable information to be provided to the user in response to received dialog interpretable instructions, thereby enabling the processor-controlled machine to conduct a dialog with the user;

dialog determining means for determining from a device class determined from information provided by the processor-controlled machine the dialog to be used with that processor-controlled machine; and

machine communication means for communicating with the processor-controlled machine to cause the processor-controlled machine to carry out a function in accordance with the dialog with the user.

6. A control apparatus according to claim 5, wherein the control apparatus is couplable to a network and the dialog determining means is arranged to determine from the device class the location on the network of a file for the dialog for that processor-controlled machine.

7. A control apparatus according to claim 5, further comprising storing means for causing the dialog to be stored in a dialog store of the control apparatus.

8. A control apparatus according to claim 5, comprising function determining means for using the JAVA reflection API to determine from the device class information regarding the processor-controlled machine functions available on that processor-controlled machine.

9. A control apparatus for enabling a user to control by spoken commands a function of a processor-controlled machine couplable to speech processing apparatus, the control apparatus comprising a JAVA virtual machine having:

receiving means for receiving dialog interpretable instructions derived from speech data processed by the speech processing apparatus;

dialog interpreting means for interpreting, using a dialog compatible with the processor-controlled machine, received dialog interpretable instructions;

dialog communication means for communicating with the processor-controlled machine using the dialog to enable information to be provided to the user in response to received dialog interpretable instructions, thereby enabling the processor-controlled machine to conduct a dialog with the user;

device interface means for receiving from the processor-controlled machine information identifying or

20250426

85  
#6

representing the device class for that processor-controlled machine;

function determining means for using the JAVA reflection API to determine from the device class information regarding the processor-controlled machine functions available on that processor-controlled machine; and

machine communication means for communicating with the processor-controlled machine to cause the processor-controlled machine to carry out a function in accordance with the dialog with the user.

10. A control apparatus according to claim 5, having a job listener registering means for registering a job listener to receive from the processor-controlled machine information relating to events occurring at the machine.

11. A control apparatus according to claim 1, wherein a dialog has a number of dialog states and the dialog communication means is arranged to control the dialog state in accordance with received dialog interpretable instructions.

12. A control apparatus according to claim 1, wherein the dialog communication means is arranged to supply to

09312426350

SUB  
A6

the speech processing apparatus information relating to the speech recognition grammar or grammars to be used for processing speech data in accordance with a dialog state.

5 13. A control apparatus according to claim 1, comprising audio data receiving means for receiving speech data and audio data transmitting means for transmitting received speech data to the speech processing apparatus.

10 14. A control apparatus according to claim 1, comprising network interface means for communicating with the speech processing apparatus over a network.

15 15. A control apparatus according to claim 1, comprising network interface means for communicating with a processor-controlled machine over a network.

20 16. A control apparatus according to claim 1, comprising remote communication means for communicating with a least one of the speech processing apparatus and a processor-controlled machine.

17. A control device comprising a control apparatus according to claim 1 and an audio input device.

Sub  
A7

```

    speech/recognising means for recognising speech in
received audio data using at least one speech recognition
grammar;

```

transmitting means for transmitting the dialog interpretable instructions to the dialog communication means.

machine control circuitry for carrying out at least one function;

storing means for storing information for at least one of a dialog file and a device class;

a processor for controlling the machine control circuitry; and

means for providing said information to the control  
apparatus for enabling the dialog determining means to

**SECRET**

*Sub  
AN* determine the dialog to be used with the processor-controlled machine.

5 20. A processor-controlled machine arranged to be connected to a control apparatus in accordance with claim 1, wherein the processor-controlled machine comprises;  
machine control circuitry for carrying out at least one function;

10 storing means for storing a device class for the processor-controlled machine;

a processor for controlling the machine control circuitry; and

15 means for supplying the device class to the control apparatus.

21. A processor-controlled machine according to claim 19, capable of providing at least one of photocopying, facsimile and printing functions.

*Sub  
AS* 20 22. A processor-controlled machine according to claim 19, comprising at least one of:

a television receiver, a video cassette recorder, a microwave oven, a digital camera, a printer, a photocopier, a facsimile machine, a lighting system, a  
25 heating system.



548  
A8

23. A device couplable to a network comprising a processor-controlled machine in accordance with claim 19 and a control apparatus in accordance with claim 1.

5 24. A device according to claim 23, wherein the control apparatus, control device or controller is integrated with the processor-controlled machine.

10 25. A device according to claim 23, comprising a separate audio input device.

FOI 200-2426860

548  
A8

15 26. A system comprising a plurality of devices in accordance with claim 23, and a speech processing apparatus connectable to the devices via a network and comprising:

means for receiving audio data representing speech by a user;

speech recognition means for recognising speech in the received audio data;

20 speech interpreting means for interpreting the recognised speech to provide dialog interpretable instructions; and

25 transmitting means for transmitting the dialog interpretable instructions over the network to at least one of said devices.

27. A system according to claim 26, further comprising a look-up service connectable to the network.

Sub  
A10  
28. In a control apparatus enabling a user to control by spoken commands a function of a processor-controlled machine couplable to speech processing apparatus, a method comprising;

determining from information provided by the processor-controlled machine a dialog to be used with that processor-controlled machine;

receiving dialog interpretable instructions derived from speech processed by the speech processing apparatus;

interpreting received dialog interpretable instructions using the determined dialog; and

communicating with the processor-controlled machine using the dialog to enable the processor-controlled machine to provide information to the user in response to received dialog interpretable instructions, thereby enabling the processor-controlled machine to conduct a dialog with the user.

29. A method according to claim 28, which comprises determining the location on a network of a file for the dialog.

30. A method according to claim 28, further comprising storing the dialog in a dialog store of the control apparatus.

31. A method according to claim 28, comprising determining from information provided by the processor-controlled machine functions available on that machine.

32. In a control apparatus comprising a JAVA virtual machine for enabling a user to control by spoken commands a function of a processor-controlled machine couplable to speech processing apparatus, a method comprising:

determining from information provided by the processor-controlled machine relating to or identifying a device class for that machine a dialog to be used with that processor-controlled machine;

receiving dialog interpretable instructions derived from speech processed by the speech processing apparatus;

interpreting received dialog interpretable instructions using the dialog; and

communicating with the processor-controlled machine using the dialog to enable the processor-controlled machine to provide information to the user in response to received dialog interpretable instructions, thereby

0544-03701

5b  
A10

5b  
A10

54  
84

enabling the processor-controlled machine to conduct a dialog with the user.

5 33. A method according to claim 32, which comprises determining from the device class the location on a network of a file for the dialog for that processor-controlled machine.

10 34. A method according to claim 32, further comprising storing the dialog in a dialog store of the control apparatus.

15 35. A method according to claim 32, comprising using the JAVA reflection API to determine from the device class information regarding the processor-controlled machine functions available on that processor-controlled machine.

SD  
AD

20 36. A method according to claim 28, wherein a dialog has a number of dialog states and the dialog state is controlled in accordance with received dialog interpretable instructions.

25 37. A method according to claim 28, wherein information relating to the speech recognition grammar or grammars to be used for processing speech data is supplied to the

Sub  
AQ  
speech processing apparatus in accordance with a dialog state.

38. A method according to claim 28, further comprising receiving speech data and transmitting received speech data to the speech processing apparatus.

39. A method according to claim 28, comprising communicating with the speech processing apparatus over a network.

40. A method according to claim 28, comprising communicating with a processor-controlled machine over a network.

41. A method according to claim 28, comprising communicating via a remote communication link with at least one of the speech processing apparatus and a processor-controlled machine.

42. In a control apparatus comprising a JAVA virtual machine for enabling a user to control by spoken commands a processor-controlled machine couplable to speech processing apparatus, a method comprising:

Sub  
A12

receiving from the processor-controlled machine information regarding the device class for that processor-controlled machine;

receiving dialog interpretable instructions derived from speech processed by the speech processing apparatus;

interpreting, using a dialog compatible with the processor-controlled machine, received dialog interpretable instructions; and

communicating with the processor-controlled machine using the dialog to enable the processor-controlled machine to provide information to the user in response to received dialog interpretable instructions, thereby enabling the processor-controlled machine to conduct a dialog with the user; and using the JAVA reflection API to determine from the device class information regarding the processor-controlled machine functions available on that processor-controlled machine.

43. A computer program product comprising processor implementable instructions for configuring a processor to provide a control apparatus in accordance with any one of claim 1.

44. A computer program product comprising processor implementable instructions for configuring a processor to carry out a method in accordance with claim 28.

50  
45. A signal comprising a computer program product in accordance with claim 43.

46. A storage medium carrying a computer program product in accordance with claim 44.

47. A computer program product comprising processor implementable instructions for configuring a processor to carry out a method in accordance with claim 32.

48. A computer program product comprising processor implementable instructions for configuring a processor to carry out a method in accordance with claim 42.

FOI 290 242 F5850

10

15